

TDS/SPECIFICATION SHEET

ANTISTATMB: HPASTF103

Product description

The MB HBASTF 103 containing a combination of GMS and ethoxylated alkylamine for providing antistatic properties for polyolefins. Its use allows to obtain a fast antistatic effect combined with a long-term efficacity."

The granular shape of this MB, being very similar to that of the polyolefin resin in terms of size and density, allows an easy mixing/dispersion with the raw materials.

Specifications (Reported on CoA)

Active Content ANTISTAT	4.5-5.5%	M ASTF

Additional Typical Values

Appearance	Milky Opaque Granules	M001
Bulk Density	0.53-0.60	M003

Recommendations of use

Addition levels of MB HPASTF103 depend on various factors such as thickness of the article, expected service life, climatic conditions, presence of fillers and other additives and commonly range from 1.0-5.0%.

Contact us for your specific recommendation needs.

Packaging

MB HPASTF103 is supplied in 25 kg plastic bags on 1000 kg or 1375 kg wooden pallets.

Storage Conditions

It is recommended to avoid the exposure of MB HPASTF103 to sunlight and high temperatures for longer times as this may impair the quality of the MB. Maximum storage time is 1 year.

Contact

Address: 19 Rue du Mercure, ZI Ben Arous

2013 Ben Arous - Tunisia. Tel: +216 71 383 675 Fax: +216 71 383 716

Email: commercial@hosta-polymers.com

Ed. 01 10/06/2015

The information contained herein is based on our current knowledge and experience. A legally binding promise of certain characteristics or suitability for a concrete individual case cannot be derived from this information. The information here is not intended to release processors and users from the responsibility of carrying out their own tests and inspections in each concrete individual case.