

TDS/SPECIFICATION SHEET

PROCESSING AID MB: HPPABO102

Product description

The MB HPPABO102 is a « Processing Aid » masterbatch containing fluoro processing aids of the third generation, recommended for use as an additive for the processing of BOPP. Its use allows to:

- Increase the extrusion throughput,
- Decrease the extrusion temperatures,

The granular shape of the Processing Aid MB HPPABO102, very similar to the polyolefin resin in terms of size and density, allows an easy mixing/dispersion with the raw materials.

Specifications (Reported on CoA)

Content of Fluoro PA	3.8-4.2%	М РАВО
----------------------	----------	--------

Additional Typical Values

Appearance	Milky Opaque Granules	M001
Bulk Density	0.49-0.60	M003

Recommendations of use

Use MB HPPABO102 at levels from 0.2-1.0%.

Packaging

MB HPPABO102 is supplied in 25 kg plastic bags on 1000 kg or 1375 kg wooden pallets.

Ed. 01 14/08/2015



TDS/SPECIFICATION SHEET

Storage Conditions

It is recommended to avoid the exposure of MB HPPABO102 to sunlight and high temperatures for longer times as this may impair the quality of the MB. Storage lifetime is 1 year.

Contact

19 Rue du Mercure, ZI Ben Arous 2013 Ben Arous - Tunisia.

Tel: +216 71 383 675 Fax: +216 71 383 716

Email: commercial@hosta-polymers.com

Ed. 01 14/08/2015